

Capillary Copper Tube 毛细铜管



Copper capillary tubes are used in various applications, such as industrial refrigeration systems, air conditioning units, heat exchangers as well as in measuring and control applications.

毛细铜管的用途十分广泛，在制冷、空调和热交换器中常用作降压、截流和控制流量等。

Nominal Capillary Dimensions

Model	Nominal Imperial Size	Nominal Metric Size
TC-26	0.026" I.D. x 0.070" O.D.	0.7mm I.D. x 1.9mm O.D.
TC-31	0.031" I.D. x 0.083" O.D.	0.8mm I.D. x 2.0mm O.D.
TC-36	0.036" I.D. x 0.087" O.D.	0.9mm I.D. x 2.1mm O.D.
TC-42	0.042" I.D. x 0.093" O.D.	1.0mm I.D. x 2.2mm O.D.
TC-49	0.049" I.D. x 0.099" O.D.	1.25mm I.D. x 2.45mm O.D.
TC-50	0.050" I.D. x 0.114" O.D.	1.3mm I.D. x 2.5mm O.D.
TC-55	0.055" I.D. x 0.125" O.D.	1.4mm I.D. x 2.6mm O.D.
TC-59	0.059" I.D. x 0.112" O.D.	1.5mm I.D. x 2.7mm O.D.
TC-64	0.064" I.D. x 0.125" O.D.	1.6mm I.D. x 2.8mm O.D.
TC-70	0.070" I.D. x 0.125" O.D.	1.8mm I.D. x 3.0mm O.D.
TC-75	0.075" I.D. x 0.125" O.D.	1.9mm I.D. x 3.1mm O.D.
TC-80	0.080" I.D. x 0.145" O.D.	2.0mm I.D. x 3.2mm O.D.
TC-90	0.090" I.D. x 0.145" O.D.	2.3mm I.D. x 3.5mm O.D.

Capillary With Flare Nuts



Model	Length	Description
BFCT-900	900 mm	With 1/4" flare nuts on each end
BFCT-1200	1200 mm	
BFCT-1500	1500 mm	