



Rotary Compressor for Refrigeration

冷冻冷藏转子压缩机



* Please contact our sales staff for other models and voltage versions.

R404A LBP Horizontal

Model 型号	Displacement 排量	Rated Cooling Capacity	Power 功率	COP 能效比 W/W	Cooling Capacity at evaporating Temp.					Connection 接口尺寸	
					-40 °C	-30 °C	-20 °C	-10 °C	0 °C	Suction	Discharge
220V - 50Hz - 1 phase											
C-RHN75E4A	13.3 cc/rev.	895 W	785 W	1.14	392 W	660 W	1041 W	1525 W	2110 W	12.8 mm	8.0 mm
C-RHN110E4A	22.0 cc/rev.	1540 W	1385 W	1.24	675 W	1135 W	1791 W	2624 W	3630 W	12.8 mm	8.0 mm
C-3RH322L4AAL	32.2 cc/rev.	2000 W	1980 W	1.01	876 W	1474 W	2326 W	3408 W	4714 W	12.8 mm	9.7 mm
C-3RH463L4AAL	46.3 cc/rev.	2990 W	2670 W	1.12	1310 W	2204 W	3477 W	5095 W	7047 W	12.8 mm	9.7 mm
220V - 60Hz - 1 phase											
C-RHN75E6A	13.3 cc/rev.	1030 W	905 W	1.14	500 W	780 W	1150 W	1680 W	2100 W	12.8 mm	8.0 mm
C-RHN110E6A	22.0 cc/rev.	1700 W	1480 W	1.15	745 W	1200 W	1900 W	2800 W	3400 W	12.8 mm	8.0 mm
C-3RHC322L4AAL	32.2 cc/rev.	2550 W	2550 W	1.00	1110 W	1900 W	2900 W	4050 W	5100 W	12.8 mm	9.7 mm
380V - 50Hz - 3 phase											
C-RHN153L8A	32.2 cc/rev.	1920 W	1800 W	1.07	841 W	1415 W	2233 W	3272 W	4525 W	12.8 mm	9.7 mm
C-RHN223L8A	46.3 cc/rev.	2770 W	2440 W	1.14	1213 W	2041 W	3222 W	4720 W	6529 W	12.8 mm	9.7 mm
200V - 50/60Hz - 3 phase											
C-1RHN43E3A	9.1 cc/rev.	590 W	500 W	0.99	258 W	435 W	686 W	1005 W	1391 W	9.6 mm	8.0 mm
C-RHN78E3A	13.3 cc/rev.	980 W	795 W	1.23	429 W	722 W	1140 W	1670 W	2310 W	9.6 mm	8.0 mm
C-7RHN78L3A	14.6 cc/rev.	840 W	750 W	1.12	368 W	620 W	978 W	1433 W	1982 W	12.8 mm	8.0 mm
C-RHN113E3A	22.0 cc/rev.	1690 W	1360 W	1.24	740 W	1246 W	1965 W	2880 W	3983 W	9.6 mm	8.0 mm
C-7RHN113L3A	23.3 cc/rev.	1630 W	1470 W	1.11	714 W	1201 W	1896 W	2778 W	3842 W	12.8 mm	8.0 mm
C-RHN153L3A	32.2 cc/rev.	2380 W	2110 W	1.13	1042 W	1754 W	2768 W	4056 W	5610 W	12.8 mm	9.7 mm
C-RHN223L3A	46.3 cc/rev.	3610 W	2920 W	1.24	1581 W	2661 W	4198 W	6151 W	8509 W	12.8 mm	9.7 mm

R22 LBP Horizontal

Model 型号	Displacement 排量	Rated Cooling Capacity	Power 功率	COP 能效比 W/W	Cooling Capacity at evaporating Temp.					Connection 接口尺寸	
					-40 °C	-30 °C	-20 °C	-10 °C	0 °C	Suction	Discharge
220V - 50Hz - 1 phase											
C-RH175E4A	14.6 cc/rev.	760 W	745 W	1.02	333 W	560 W	884 W	1295 W	1791 W	12.8 mm	8.0 mm
C-RH110E4A	23.3 cc/rev.	1300 W	1210 W	1.07	569 W	958 W	1512 W	2215 W	3064 W	12.8 mm	8.0 mm
220V - 60Hz - 1 phase											
C-RH170L6A	35.9 cc/rev.	2230 W	2060 W	1.08	977 W	1644 W	2593 W	3800 W	5256 W	12.8 mm	9.7 mm
C-RH220L6A	48.6 cc/rev.	3110 W	2870 W	1.08	1362 W	2292 W	3617 W	5299 W	7330 W	12.8 mm	9.7 mm
380V - 50Hz - 3 phase											
C-RH173L8A	35.9 cc/rev.	1800 W	1700 W	1.06	788 W	1327 W	2093 W	3067 W	4243 W	12.8 mm	9.7 mm
200V - 50/60Hz - 3 phase											
C-RH150L3A	32.2 cc/rev.	1900 W	1900 W	1.00	832 W	1400 W	2210 W	3238 W	4478 W	12.8 mm	9.7 mm
C-RH173L3A	35.9 cc/rev.	2210 W	1950 W	1.13	968 W	1629 W	2570 W	3766 W	5209 W	12.8 mm	9.7 mm
C-RH223L3A	48.6 cc/rev.	2430 W	2550 W	1.13	1261 W	2123 W	3349 W	4908 W	6788 W	12.8 mm	9.7 mm

R404A MBP Horizontal

Model 型号	Displacement 排量	Rated Cooling Capacity	Power 功率	COP 能效比 W/W	Cooling Capacity at evaporating Temp.					Connection 接口尺寸	
					-40 °C	-30 °C	-20 °C	-10 °C	0 °C	Suction	Discharge
200V - 50/60Hz - 3 phase											
C-RH150L3A	32.2 cc/rev.	1900 W	1900 W	1.00	832 W	1400 W	2210 W	3238 W	4478 W	12.8 mm	9.7 mm
C-RH173L3A	35.9 cc/rev.	2210 W	1950 W	1.13	968 W	1629 W	2570 W	3766 W	5209 W	12.8 mm	9.7 mm
C-RH223L3A	48.6 cc/rev.	2430 W	2550 W	1.13	1261 W	2123 W	3349 W	4908 W	6788 W	12.8 mm	9.7 mm