

# SECOP

## Recip. Compressor 活塞式压缩机



\* Please contact our sales staff for other models and voltage versions.

R134a 220-240V / 50/60Hz | 208-230V / 60Hz

Model 型号	Application 应用	ASHRAE Capacity Tc=54.4 °C, Tliq=32.2 °C, Tsuc=32.2 °C at Evaporating Temp.						ASHRAE Cooling Capacity			Displ. 排量
		-35 °C	-15 °C	-5 °C	0 °C	10 °C	15 °C	LBP rating point -23.3 °C / 54.4 °C	MBP rating point -6.7 °C / 54.4 °C	HBP rating point 7.2 °C / 54.4 °C	
SC10G	L/M/HBP	30 W	333 W	603 W	766 W	1149 W	1368 W	168 W	493 W	923 W	10.29 cc/rev.
SC12G	L/M/HBP	81 W	433 W	749 W	954 W	1471 W	1791 W	248 W	614 W	1170 W	12.87 cc/rev.
SC15G	L/M/HBP	-	527 W	904 W	1127 W	1669 W	1998 W	260 W	745 W	1341 W	15.28 cc/rev.
SC18G	L/M/HBP	-	658 W	1081 W	1348 W	2011 W	2417 W	397 W	893 W	1612 W	17.69 cc/rev.
SC21G	L/M/HBP	-	755 W	1261 W	1579 W	2352 W	2810 W	461 W	1039 W	1889 W	20.95 cc/rev.

R404A / R507 220-240V / 50Hz

Model 型号	Application 应用	ASHRAE Capacity Tc=54.4 °C, Tliq=32.2 °C, Tsuc=32.2 °C at Evaporating Temp.						ASHRAE Cooling Capacity			Displ. 排量
		-35 °C	-15 °C	-5 °C	0 °C	10 °C	15 °C	LBP rating point -23.3 °C / 54.4 °C	MBP rating point -6.7 °C / 54.4 °C	HBP rating point 7.2 °C / 54.4 °C	
SC10CL	LBP	116 W	615 W	1014 W	-	-	-	366 W	811 W	-	10.29 cc/rev.
SC12CL	LBP	165 W	857 W	1397 W	-	-	-	516 W	1112 W	-	12.87 cc/rev.
SC15CL	LBP	180 W	1101 W	1678 W	-	-	-	697 W	1349 W	-	15.28 cc/rev.
SC15CLX.2	LBP	339 W	1097 W	-	-	-	-	724 W	-	-	15.28 cc/rev.
SC15MLX	MBP	-	1117 W	1718 W	2102 W	-	-	762 W	1375 W	2371 W	15.28 cc/rev.
SC18CL	LBP	374 W	1220 W	1882 W	-	-	-	803 W	1508 W	-	17.69 cc/rev.
SC18MLX	MBP	-	1306 W	2001 W	2446 W	-	-	894 W	1603 W	2757 W	17.69 cc/rev.
SC18MLX.3	MBP	-	1384 W	2097 W	2552 W	-	-	959 W	1683 W	2862 W	17.68 cc/rev.
SC21CL	LBP	442 W	1386 W	-	-	-	-	905 W	-	-	20.95 cc/rev.

R404A / R507 220-240V / 50/60Hz | 208-230V / 60Hz

Model 型号	Application 应用	ASHRAE Capacity Tc=54.4 °C, Tliq=32.2 °C, Tsuc=32.2 °C at Evaporating Temp.						ASHRAE Cooling Capacity			Displ. 排量
		-35 °C	-15 °C	-5 °C	0 °C	10 °C	15 °C	LBP rating point -23.3 °C / 54.4 °C	MBP rating point -6.7 °C / 54.4 °C	HBP rating point 7.2 °C / 54.4 °C	
SC10CLX	L/MBP	130 W	655 W	1064 W	-	-	-	369 W	847 W	-	10.29 cc/rev.
SC10MLX	MBP	-	722 W	1127 W	1380 W	-	-	-	902 W	1553 W	10.29 cc/rev.
SC12CLX.2	LBP	278 W	899 W	-	-	-	-	593 W	-	-	12.87 cc/rev.
SC12MLX	MBP	-	886 W	1369 W	1670 W	-	-	584 W	1096 W	1873 W	12.87 cc/rev.

R290 220-240V / 50/60Hz | 208-230V / 60Hz

Model 型号	Application 应用	ASHRAE Capacity Tc=54.4 °C, Tliq=32.2 °C, Tsuc=32.2 °C at Evaporating Temp.						ASHRAE Cooling Capacity			Displ. 排量
		-35 °C	-15 °C	-5 °C	0 °C	10 °C	15 °C	LBP rating point -23.3 °C / 54.4 °C	MBP rating point -6.7 °C / 54.4 °C	HBP rating point 7.2 °C / 54.4 °C	
SC18CNLX.2	LBP	457 W	1268 W	1823 W	-	-	-	922 W	1533 W	-	17.69 cc/rev.
SC21CNLX.2	LBP	570 W	1552 W	2201 W	-	-	-	1138 W	1856 W	-	20.95 cc/rev.

R290 220-240V / 50Hz

Model 型号	Application 应用	ASHRAE Capacity Tc=54.4 °C, Tliq=32.2 °C, Tsuc=32.2 °C at Evaporating Temp.						ASHRAE Cooling Capacity			Displ. 排量
		-35 °C	-15 °C	-5 °C	0 °C	10 °C	15 °C	LBP rating point -23.3 °C / 54.4 °C	MBP rating point -6.7 °C / 54.4 °C	HBP rating point 7.2 °C / 54.4 °C	
SC10CNX	L/MBP	175 W	547 W	853 W	1042 W	-	-	358 W	711 W	-	10.29 cc/rev.
SC12CNX	L/MBP	227 W	711 W	1110 W	1372 W	-	-	475 W	923 W	-	12.87 cc/rev.
SC15CNX	L/MBP	251 W	918 W	1415 W	1717 W	-	-	597 W	1183 W	-	15.28 cc/rev.
SC18CNX	L/MBP	315 W	1106 W	1684 W	2032 W	-	-	727 W	1410 W	-	17.69 cc/rev.
SC12CNX.2	LBP	230 W	742 W	-	-	-	-	491 W	-	-	12.87 cc/rev.
SC12CNX.2	LBP	345 W	928 W	-	-	-	-	624 W	-	-	15.28 cc/rev.
SC15CNX.2	LBP	342 W	1194 W	-	-	-	-	797 W	-	-	17.69 cc/rev.
SC18CNX.2	LBP	462 W	1399 W	-	-	-	-	962 W	-	-	20.95 cc/rev.