

Shaded Pole Motor 罩极电机



FEATURES:

Standard oil bearings, ball bearing is optional.
Thermal protector for motors above 10W,
impedance protection for motors below 10W.

- * Working mode: continuous S1
- * Insulation Class B
- * Protection Class: IP42, IP44
- * Ambient temp.: -30°C to +60°C
- * Low power consumption

罩极电机标准配置为含油轴承，滚珠轴承可选。
输出功率大于 10W 的电机配备热保护器；输出
功率在 10W 以下的电机采用阻抗保护。

- * 运行方式：连续 S1
- * 绝缘等级：B 级
- * 防护等级：IP42, IP44
- * 运行环境温度：-30°C to +60°C
- * 低能耗

Model 型号	Rated Voltage 额定电压	Frequency 频率	Rated Input 额定功率	Output 输出功率	Current 电流	Speed 转速	Fan Blade 风页	Bracket 支架
YZ5-13	220 - 240 V	50 / 60 Hz	33 W	5 W	0.21 A	1300 RPM	Ø 200 mm	H72
	110 - 120 V	60 Hz	33 W	5 W	0.55 A	1550 RPM	Ø 200 mm	H72
YZ7-20	220 - 240 V	50 / 60 Hz	38 W	7 W	0.23 A	1300 RPM	Ø 230 mm	H84
	110 - 120 V	60 Hz	40 W	10 W	0.80 A	1550 RPM	Ø 230 mm	H84
YZ10-20	220 - 240 V	50 / 60 Hz	40 W	10 W	0.25 A	1300 RPM	Ø 230 mm	H84
	110 - 120 V	60 Hz	40 W	10 W	0.80 A	1550 RPM	Ø 230 mm	H84
YZ16-25	220 - 240 V	50 / 60 Hz	70 W	16 W	0.45 A	1300 RPM	Ø 250 mm	H84
	110 - 120 V	60 Hz	70 W	16 W	1.01 A	1550 RPM	Ø 250 mm	H84
YZ18-30	220 - 240 V	50 / 60 Hz	75 W	18 W	0.50 A	1300 RPM	Ø 250 mm	H109-1
	110 - 120 V	60 Hz	75 W	18 W	1.10 A	1550 RPM	Ø 250 mm	H109-1
YZ25-40	220 - 240 V	50 / 60 Hz	100 W	25 W	0.70 A	1300 RPM	Ø 300 mm	H109-1
	110 - 120 V	60 Hz	100 W	25 W	1.40 A	1550 RPM	Ø 300 mm	H109-1
YZ24-30	220 - 240 V	50 / 60 Hz	120 W	34 W	0.85 A	1300 RPM	Ø 300 mm	H109-1
	110 - 120 V	60 Hz	120 W	34 W	1.50 A	1550 RPM	Ø 300 mm	H109-1

Mounting Type



NO Mounting Screws



Mounting Screws
Distance: 18 or 26mm



Mounting Screws
Distance: 18 and 26mm