

## Tangential Fan 贯流风机



### FEATURES:

- \* Aluminum impeller
- \* Working temp.: 0°C to +60°C
- \* Insulation class B or class F
- \* CE qualified
- \* Lead wire or terminal for option
- \* 铝制风页轮
- \* 运行环境温度: 0°C to +60°C
- \* 绝缘等级: B 级或 F 级
- \* CE 认证
- \* 可选引线式或插片式

Model	Impeller Dia.	Rated Volt.	Freq.	Current	Input	Speed	Air Flow	Noise
MTTF-30.90	30 mm	230 V	50 Hz	0.06 A	8.5 W	2800 RPM	40 m <sup>3</sup> /h	35 dB(A)
MTTF-30.120	30 mm	230 V	50 Hz	0.10 A	15.0 W	2800 RPM	55 m <sup>3</sup> /h	36 dB(A)
MTTF-30.240	30 mm	230 V	50 Hz	0.11 A	16.0 W	2800 RPM	100 m <sup>3</sup> /h	37 dB(A)
MTTF-30.300	30 mm	230 V	50 Hz	0.10 A	16.0 W	2800 RPM	120 m <sup>3</sup> /h	39 dB(A)
MTTF-40.120	40 mm	230 V	50 Hz	0.08 A	13.0 W	2750 RPM	90 m <sup>3</sup> /h	35 dB(A)
MTTF-40.180	40 mm	230 V	50 Hz	0.13 A	21.0 W	2700 RPM	140 m <sup>3</sup> /h	36 dB(A)
MTTF-40.240	40 mm	230 V	50 Hz	0.11 A	17.5 W	2700 RPM	190 m <sup>3</sup> /h	37 dB(A)
MTTF-40.300	40 mm	230 V	50 Hz	0.13 A	21.0 W	2700 RPM	230 m <sup>3</sup> /h	39 dB(A)
MTTF-45.180	45 mm	230 V	50 Hz	0.10 A	12.5 W	1300 RPM	64 m <sup>3</sup> /h	45 dB(A)
MTTF-45.240	45 mm	230 V	50 Hz	0.22 A	23.0 W	1600 RPM	135 m <sup>3</sup> /h	45 dB(A)
MTTF-45.300	45 mm	230 V	50 Hz	0.19 A	22.5 W	1300 RPM	107 m <sup>3</sup> /h	41 dB(A)
MTTF-50.120	50 mm	230 V	50 Hz	0.08 A	15.0 W	2500 RPM	130 m <sup>3</sup> /h	40 dB(A)
MTTF-50.180	50 mm	230 V	50 Hz	0.23 A	20.0 W	2650 RPM	210 m <sup>3</sup> /h	41 dB(A)
MTTF-50.240	50 mm	230 V	50 Hz	0.11 A	20.0 W	2200 RPM	220 m <sup>3</sup> /h	42 dB(A)
MTTF-50.300	50 mm	230 V	50 Hz	0.13 A	22.0 W	2200 RPM	270 m <sup>3</sup> /h	45 dB(A)