

Hand Torch 焊枪



Handle Torch HT-S3

- * Safety tip with dia. 9.7mm as standard nozzle
- * Temperature can reach 1650°C
- * 360° rotation of swivel tip operates in any position, even upside down
- * Features trigger lock with instant safety release



Handle Torch HT-1S

- * Stainless steel tip
- * Temperature can reach 1650°C
- * 360° rotation of swivel tip operates in any position, even upside down
- * Temperature control valve



Handle Torch HT-1

- * Stainless steel tip
- * Temperature can reach 1650°C
- * 360° rotation of swivel tip operates in any position, even upside down
- * Temperature control valve



Handle Torch HT-T2

- * Stainless steel tip (double tube)
- * Temperature can reach 1650°C
- * 360° rotation of swivel tip operates in any position, even upside down
- * Temperature control valve



Handle Torch HT-1S660

- * Stainless steel tip
- * Temperature can reach 1650°C
- * 360° rotation of swivel tip operates in any position, even upside down
- * Temperature control valve
- * 1.5m flexible hose

MAP-PRO, PROPANE



Item	Description	Units per Case
MAP Pro	<ul style="list-style-type: none"> * 14.1 oz. (400gr.) MAP-Pro * Extremely high flame temperature, utmost burning performance and guaranteed short working times * Easy to use, increased user safety through improved valve * Burns longer and hotter than propane 	12 units
Propane	<ul style="list-style-type: none"> * 14.1 oz. (400gr.) Propane * Industrial grade gas in tough impact resistant disposable steel cylinders, for high performance soldering work 	12 units