

Vacuum Pump 真空泵



FEATURES:

- * Compact design
- * Built-in check valve prevents oil back flow during power failure
- * Large oil sight glass
- * Oil reservoir helps reduce operating temp.
- * 体积小，轻量化设计
- * 内置止回阀
- * 大口径油视镜方便观察
- * 内置储油器可降低工作油温

Single Stage Vacuum Pump

| Model | Flow Rate | | Ultimate Vacuum | Power | Inlet Port | Oil Cap. | Dimensions | Weight |
|---------|----------------------|----------------------|-----------------|--------|-------------------|----------|--------------------|---------|
| | 50 Hz | 60 Hz | | | | | | |
| VP115B | 1.5 cfm (42 l/min) | 1.8 cfm (50 l/min) | 150 microns | 1/4 hp | 1/4" flare | 320 ml | 270 x 119 x 216 mm | 4.6 kg |
| VP125B | 2.5 cfm (70 l/min) | 3.0 cfm (84 l/min) | 150 microns | 1/4 hp | 1/4" flare | 300 ml | 270 x 119 x 216 mm | 5.0 kg |
| VP135B | 3.5 cfm (100 l/min) | 4.0 cfm (114 l/min) | 150 microns | 1/3 hp | 1/4" flare | 330 ml | 278 x 119 x 216 mm | 5.6 kg |
| VP145B | 4.5 cfm (128 l/min) | 5.0 cfm (142 l/min) | 150 microns | 1/3 hp | 1/4" flare | 320 ml | 278 x 119 x 216 mm | 6.0 kg |
| VP160B | 6.0 cfm (170 l/min) | 7.0 cfm (198 l/min) | 150 microns | 1/2 hp | 1/4" flare | 450 ml | 320 x 134 x 232 mm | 7.8 kg |
| VP180B | 8.0 cfm (226 l/min) | 9.0 cfm (254 l/min) | 150 microns | 3/4 hp | 1/4" & 3/8" flare | 650 ml | 370 x 140 x 250 mm | 12.3 kg |
| VP1100B | 10.0 cfm (283 l/min) | 12.0 cfm (340 l/min) | 150 microns | 1 hp | 1/4" & 3/8" flare | 800 ml | 390 x 140 x 250 mm | 12.8 kg |

Dual Stage Vacuum Pump

| Model | Flow Rate | | Ultimate Vacuum | Power | Inlet Port | Oil Cap. | Dimensions | Weight |
|---------|----------------------|----------------------|-----------------|--------|-------------------|----------|--------------------|---------|
| | 50 Hz | 60 Hz | | | | | | |
| VP215B | 1.5 cfm (42 l/min) | 1.8 cfm (50 l/min) | 25 microns | 1/4 hp | 1/4" flare | 250 ml | 270 x 119 x 216 mm | 6.0 kg |
| VP225B | 2.5 cfm (70 l/min) | 3.0 cfm (84 l/min) | 25 microns | 1/3 hp | 1/4" flare | 280 ml | 278 x 119 x 216 mm | 6.8 kg |
| VP235B | 3.5 cfm (100 l/min) | 4.0 cfm (114 l/min) | 25 microns | 1/3 hp | 1/4" flare | 420 ml | 320 x 134 x 232 mm | 8.2 kg |
| VP245B | 4.5 cfm (128 l/min) | 5.0 cfm (142 l/min) | 25 microns | 1/2 hp | 1/4" flare | 400 ml | 320 x 134 x 232 mm | 8.5 kg |
| VP260B | 6.0 cfm (170 l/min) | 7.0 cfm (198 l/min) | 25 microns | 3/4 hp | 1/4" & 3/8" flare | 500 ml | 370 x 140 x 250 mm | 13.5 kg |
| VP280B | 8.0 cfm (226 l/min) | 9.0 cfm (254 l/min) | 25 microns | 1 hp | 1/4" & 3/8" flare | 500 ml | 370 x 140 x 250 mm | 14.0 kg |
| VP2100B | 10.0 cfm (283 l/min) | 12.0 cfm (340 l/min) | 25 microns | 1 hp | 1/4" & 3/8" flare | 700 ml | 390 x 140 x 250 mm | 14.5 kg |

Power Plug & Adapters

