

## Ball Valve 球阀



Model 型号			Conn. 接口
Without access 不带充注阀	Access port on copper tube 充注阀在铜管上	Access port on valve body 充注阀在阀体上	
VABV-202	VABV-202A	GBV2	1/4" ODF
VABV-203	VABV-203A	GBV3	3/8" ODF
VABV-204	VABV-204A	GBV4	1/2" ODF
VABV-205	VABV-205A	GBV5	5/8" ODF
VABV-206	VABV-206A	GBV6	3/4" ODF
VABV-207	VABV-207A	GBV7	7/8" ODF
VABV-209	VABV-209A	GBV9	1-1/8" ODF
VABV-211	VABV-211A	GBV11	1-3/8" ODF
VABV-213	VABV-213A	GBV13	1-5/8" ODF
VABV-217	VABV-217A	GBV17	2-1/8" ODF
VABV-221	VABV-221A	-	2-5/8" ODF
VABV-225	VABV-225A	-	3-1/8" ODF

- \* Compatible with CFC, HCFC, HFC and HFO refrigerants and oils
- \* Forged brass body, easy flow no pressure drop
- \* Access port is optional
- \* Working temp.: -40°C to +150°C
- \* Max. working pressure: 4.5 MPa

- \* 适用于所有 CFC、HCFC 和 HFC 制冷剂及冷冻油
- \* 锻造黄铜阀体，坚固耐用的同时实现最大流量和最小压降
- \* 可选配充注阀口款式
- \* 工作温度: -40°C to +150°C
- \* 最大工作压力: 4.5 MPa