

FDBK series Bi-flow Filter Drier FDBK 系列双向干燥过滤器



FEATURES:

- * Integrated check valve insures Bi-flow capability, eliminate the need for external check valves and reduce the external piping
- * Max. working pressure 45 bar
- * Compatible with CFC, HCFC and HFC refrigerants
- * Corrosion resistant epoxy powder coating
- * 双向干燥过滤器其内置的单向阀可保证制冷剂从滤芯外向滤芯内流动，不需要另配外部单向阀
- * 最大工作压力为 45 bar
- * 适用于 CFC, HCFC 和 HFC 制冷剂
- * 表面涂层采用抗腐蚀的环氧粉末喷涂

Model	Connection	Nominal Flow Capacity (kW) at 0.07 bar pressure drop			Dimension			
		R22	R410A	R407C	A	B	D	L
FDBK-052	1/4 SAE	5.6	5.6	5.6	22.5 mm	76.0 mm	63.5 mm	121 mm
FDBK-052S	1/4 ODF	7.7	7.7	7.7	18.0 mm			112 mm
FDBK-053	3/8 SAE	12.4	12.4	12.0	27.5 mm			131 mm
FDBK-053S	3/8 ODF	13.8	13.8	13.6	19.0 mm	100.0 mm	63.5 mm	114 mm
FDBK-082	1/4 SAE	7.0	7.0	6.9	22.5 mm			145 mm
FDBK-082S	1/4 ODF	7.8	7.8	7.4	18.0 mm			136 mm
FDBK-083	3/8 SAE	15.8	15.8	15.4	27.5 mm			155 mm
FDBK-083S	3/8 ODF	17.8	17.8	17.4	19.0 mm			138 mm
FDBK-084	1/2 SAE	22.5	22.5	22.1	30.0 mm			160 mm
FDBK-084S	1/2 ODF	23.6	23.6	23.2	20.0 mm			140 mm
FDBK-085	5/8 SAE	27.4	27.4	26.6	35.0 mm			170 mm
FDBK-085S	5/8 ODF	28.5	28.5	27.8	24.0 mm			148 mm
FDBK-162	1/4 SAE	8.1	8.8	8.4	22.5 mm			110.0 mm
FDBK-162S	1/4 ODF	10.9	12.0	11.6	18.0 mm	146 mm		
FDBK-163	3/8 SAE	16.2	16.2	15.8	27.5 mm	165 mm		
FDBK-163S	3/8 ODF	18.3	18.3	17.9	19.0 mm	148 mm		
FDBK-164	1/2 SAE	27.1	27.1	26.7	30.0 mm	170 mm		
FDBK-164S	1/2 ODF	28.5	28.5	27.8	20.0 mm	150 mm		
FDBK-165	5/8 SAE	29.2	29.2	28.5	35.0 mm	180 mm		
FDBK-165S	5/8 ODF	30.6	30.6	29.9	24.0 mm	158 mm		
FDBK-166	3/4 SAE	34.5	34.5	33.6	40.0 mm	190 mm		
FDBK-166S	3/4 ODF	36.6	36.6	35.9	26.0 mm	162 mm		
FDBK-167S	7/8 ODF	40.2	40.2	39.6	28.5 mm	167 mm		
FDBK-303	3/8 SAE	18.3	18.3	17.9	27.5 mm	181.0 mm	76.0 mm	236 mm
FDBK-303S	3/8 ODF	20.4	20.4	20.0	19.0 mm			219 mm
FDBK-304	1/2 SAE	26.8	26.8	26.4	30.0 mm			241 mm
FDBK-304S	1/2 ODF	34.1	34.1	33.4	20.0 mm			221 mm
FDBK-305	5/8 SAE	36.3	36.3	35.5	35.0 mm			251 mm
FDBK-305S	5/8 ODF	50.0	50.0	48.9	24.0 mm			229 mm
FDBK-306	3/4 SAE	43.0	43.0	40.2	40.0 mm			261 mm
FDBK-306S	3/4 ODF	56.3	56.3	55.3	26.0 mm			233 mm
FDBK-307S	7/8 ODF	58.8	58.8	57.7	28.5 mm			238 mm
FDBK-309S	1-1/8 ODF	68.9	68.9	67.8	29.0 mm			239 mm