

Condensate Drain Pump 冷凝排水泵



Model	PC-125A	PC-125L	PC-250A	PC-320A
Voltage	230V 50/60Hz or 115V 60Hz	230V 50/60Hz or 115V 60Hz	100-230V 50/60Hz	100-230V 50/60Hz
Max Discharge Head	4 m (13 ft.)	4 m (13 ft.)	4.2 m (14 ft.)	6 m (20 ft.)
Flow Rate	125 L/hr. (33 gallon/hr.)	125 L/hr. (33 gallon/hr.)	250 L/hr. (66 gallon/hr.)	320 L/hr. (85 gallon/hr.)
Tank Capacity	1.8 L	1.0 L	1.0 L	1.8 L
Sound Level	48 dB(A)	48 dB(A)	26 dB(A)	28 dB(A)
Power Consumption	60 W	60 W	15 W	20 W
Dimensions	286 x 136 x 166 mm	286 x 136 x 140 mm	210 x 100 x 116 mm	286 x 126 x 125 mm



Model	PC-12B	PC-36B	PC-24B	PC-40B
Voltage	100-230V 50/60Hz	100-230V 50/60Hz	100-230V 50/60Hz	100-230V 50/60Hz
Max Discharge Head	10 m (33 ft.)	10 m (33 ft.)	10 m (33 ft.)	10 m (33 ft.)
Flow Rate	18 L/hr. (4.8 gallon/hr.)	36 L/hr. (9.6 gallon/hr.)	24 L/hr. (6.2 gallon/hr.)	40 L/hr. (10.5 gallon/hr.)
Tank Capacity	35 mL	35 mL	55 mL	55 mL
Sound Level	19 dB(A)	21 dB(A)	19 dB(A)	21 dB(A)
Power Consumption	3 W	3 W	3 W	3 W