

Electronical Control Box 电控箱

ECB-1000 series plastic control box



| |
|---|
| Description |
| Power supply: 100-250V, 50/60Hz |
| Temp. control: -40 to +99 °C |
| Accuracy: ± 0.1 °C (-20 to +50 °C); ± 0.3 °C other |
| Resolution: 0.1 °C |
| Sensor cable length: 2 m |
| Storage temp.: -20 °C to +75 °C |
| Ambient temp.: -10 °C to +65 °C |
| Dimension: 265 x 167.5 x 92 mm |
| Protection IP65 |

ECB-2000 series plastic control box



| |
|---|
| Description |
| Power supply: 380V, 50/60Hz |
| Compressor power: 5 HP (18A), 10 HP (25A), 15 HP (32 A) |
| Temp. control: -40 to +85 °C |
| Accuracy: ± 1 °C |
| Resolution: 0.1 °C |
| Sensor cable length: 2 m |
| Ambient temp.: -10 °C to +60 °C |
| Dimension: 380 x 329 x 140 mm |
| Protection IP65 |

ECB-5060 control box



| |
|---|
| Description |
| Power supply: 380V, 50/60Hz |
| Temp. control: -50 to +50 °C |
| Compressor power: 5HP (18A), 10HP (25A), 15HP (32A), 20HP (40A), 25HP (50A), 30HP (65A) |
| Accuracy: ± 0.1 °C |
| Resolution: 0.1 °C |
| Sensor cable length: 2 m |
| Storage temp.: -50 °C to +50 °C |
| Ambient temp.: -10 °C to +60 °C |
| Dimension: 340 x 420 x 135 mm (5-15HP), 350 x 470 x 180mm (20-30HP) |
| Protection IP65 |

ECB-5080 control box



| |
|---|
| Description |
| Power supply: 380V, 50/60Hz |
| Temp. control: -50 to +50 °C |
| Compressor power: 5HP (18A), 10HP (25A), 15HP (32A), 20HP (40A), 25HP (50A), 30HP (65A) |
| Accuracy: ± 0.1 °C |
| Resolution: 0.1 °C |
| Sensor cable length: 2 m |
| Storage temp.: -50 °C to +50 °C |
| Ambient temp.: -10 °C to +60 °C |
| Dimension: 340 x 420 x 135 mm (5-15HP), 400 x 550 x 180mm (20-30HP) |
| Protection IP65 |