

## Hand Valve 手阀



| Model<br>型号 | Conn. Size<br>接口尺寸 | Conn. Type<br>接口类型             |
|-------------|--------------------|--------------------------------|
| VAHV-1/4F   | 1/4"               | flare to flare, with brass nut |
| VAHV-3/8F   | 3/8"               | flare to flare, with brass nut |
| VAHV-1/2F   | 1/2"               | flare to flare, with brass nut |
| VAHV-5/8F   | 5/8"               | flare to flare, with brass nut |
| VAHV-3/4F   | 3/4"               | flare to flare, with brass nut |
| VAHV-1/4S   | 1/4"               | solder to solder               |
| VAHV-3/8S   | 3/8"               | solder to solder               |
| VAHV-1/2S   | 1/2"               | solder to solder               |
| VAHV-5/8S   | 5/8"               | solder to solder               |
| VAHV-3/4S   | 3/4"               | solder to solder               |

- \* Compatible with CFC, HCFC, HFC and HFO refrigerants and oils
- \* Forged brass body with full size openings for maximum flow and minimum pressure drop
- \* Thermally stable hand wheel for operation in wide temperature ranges
- \* Working temp.: -40°C to +130°C

- \* 适用于所有 CFC、HCFC 和 HFC 制冷剂及冷冻油
- \* 锻造黄铜阀体，坚固耐用的同时实现最大流量和最小压降
- \* 耐热手柄适用于各类环境工况
- \* 工作温度：-40°C to +130°C