

## Refrigerant Recovery Machine 冷媒回收机



### FEATURES:

- \* Multi-functional valve design, automatic clearance of remaining refrigerants
- \* "Super cool" fan and efficient condenser design, speed up the recycling and filling
- \* Pull rod design, convenient for taking out
- \* Automatic safety shut-off: 38.5 bar (559 psi)
- \* Compressor: oil-less, air-cooled

Model	TRR 12A (TRR 12B*, TRR 12C**)			TRR 24A (TRR 24B*, TRR 24C**)			
Power Supply	220-240V 50/60Hz		115V 60Hz	220-240V 50/60Hz		115V 60Hz	
Motor Power	3/4 HP		3/4 HP	1 HP		1 HP	
Motor Speed	1450 rpm / 1750 rpm		1750 rpm	1450 rpm / 1750 rpm		1750 rpm	
Max. Current	4 A		8 A	5 A		10 A	
Recovery Rate	Category	III	IV	V	III	IV	V
	Vapor	0.2 kg/min.	0.25 kg/min.	0.25 kg/min.	0.4 kg/min.	0.5 kg/min.	0.5 kg/min.
	Liquid	1.6 kg/min.	1.8 kg/min.	2.2 kg/min.	3.0 kg/min.	3.5 kg/min.	3.5 kg/min.
	Push / Pull	4.6 kg/min.	5.6 kg/min.	6.3 kg/min.	7.5 kg/min.	8.5 kg/min.	9.5 kg/min.
Dimensions	465 x 225 x 360 mm			465 x 225 x 360 mm			
Weight	15.5 kg			16.8 kg			

\* Models with oil-gas separator; \*\* Models with pressure protection.

Category: III R12, R134a, R401C, R500;

IV R22, R401A, R401B, R402B, R407C, R407D, R408A, R409A, R411A, R411B, R412A, R502, R509;

V R402A, R404A, R407A, R407B, R410A, R507