

Cold Storage Lamp

冷库专用灯

Haiding's LED lamps are specially designed for cold storage, up to IP68 rated and permanently sealed preventing water or debris. With ambient working temperature range from -40°C to 55°C, those LED lamps have significantly longer service lifetime and save up to 60% energy cost.

冷库专用 LED 灯是为适应冷库内长期低温和潮湿的工况而设计的。防水等级高达 IP68 的优异性能可有效隔绝水气或其它异物侵入 LED 灯组内部，工作温度范围为 -40°C 至 55°C，相比于普通 LED 灯具具有更长的使用寿命，并可节省 60% 的用电量。

Oval Type



FEATURES:

- * Working life: >50000hr.
- * IP68 protection
- * Working temp.: -40°C to +50°C

| Model | CSL-301 | CSL-401 | CSL-415 |
|-------------------|----------------------|----------------------|----------------------|
| LED Q'ty | 40 pcs | 48 pcs | 36 pcs |
| Rated Power | 10 W | 8 W | 15 W |
| Voltage | 36 V, 110 V or 220 V | 36 V, 110 V or 220 V | 36 V, 110 V or 220 V |
| Frequency | 50/60 Hz | 50/60 Hz | 50/60 Hz |
| Color Temperature | 6500 K | 6500 K | 6500 K |

Square Type



FEATURES:

- * Working life: >50000hr.
- * IP68 protection
- * Working temp.: -40°C to +50°C

| Model | CSL-307 | CSL-407 |
|-------------------|----------------------|----------------------|
| LED Q'ty | 100 pcs | 100 pcs |
| Rated Power | 20 W | 20 W |
| Voltage | 36 V, 110 V or 220 V | 36 V, 110 V or 220 V |
| Frequency | 50/60 Hz | 50/60 Hz |
| Color Temperature | 6500 K | 6500 K |

Rectangle Type



FEATURES:

- * Working life: >50000hr.
- * IP68 protection
- * Working temp.: -40°C to +50°C
- * CCC recognized

| Model | CSL-401 | CSL-402 | CSL-403 |
|-------------------|--------------|--------------|--------------|
| LED Q'ty | 40 pcs | 40 pcs | 40 pcs |
| Rated Power | 8 W | 10 W | 12 W |
| Voltage | 220 V | 220 V | 220 V |
| Frequency | 50 Hz | 50 Hz | 50 Hz |
| Color Temperature | 6500 -7000 K | 6500 -7000 K | 6500 -7000 K |

Round Type



FEATURES:

- * Working life: >50000hr.
- * IP68 protection
- * Working temp.: -40°C to +50°C
- * CCC recognized

| Model | CSL-415Y | CSL-418Y |
|-------------------|--------------|--------------|
| LED Q'ty | 42 pcs | 42 pcs |
| Rated Power | 15 W | 18 W |
| Voltage | 220 V | 220 V |
| Frequency | 50 Hz | 50 Hz |
| Color Temperature | 6500 -7000 K | 6500 -7000 K |